MJE13007

NPN SILICON TRANSISTOR

NPN BIPOLAR POWER TRANSISTOR FOR SWITCHING POWER SUPPLY APPLICATIONS



TO-220



TO-220F

*Pb-free plating product number: MJE13007L

■ DESCRIPTION

The UTC **MJE13007** is designed for high–voltage, high–speed power switching inductive circuits where fall time is critical. It is particularly suited for 115 and 220 V switch mode applications.

■ FEATURES

* $V_{CEO(SUS)}$ 400 V
* 700 V Blocking Capability

■ ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Normal	Lead Free Plating		1	2	3	
MJE13007-TA3-T	MJE13007L-TA3-T	TO-220	B	C	E	Tube
MJE13007-TF3-T	MJE13007L-TF3-T	TO-220F	B	C	E	Tube

MJE13007L-TA3-T (1)Packing Type (2)Package Type (3)Lead Plating	(1)T: Tube (2) TA3: TO-220, TF3: TO-220F (3) L: Lead Free Plating, Blank: Pb/Sn

Copyright © 2005 Unisonic Technologies Co., Ltd

■ ABSOLUTE MAXIMUM RATING

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Emitter Sustaining Voltage		V_{CEO}	400	V
Collector-Emitter Breakdown Voltage		V_{CBO}	700	V
Emitter-Base Voltage		V_{EBO}	9.0	V
Collector Current	Continuous	I_C	8.0	A
	Peak (1)	I_{CM}	16	A
Base Current	Continuous	I_B	4.0	A
	Peak (1)	I_{BM}	8.0	A
Emitter Current	Continuous	I_E	12	A
	Peak (1)	I_{EM}	24	A
Total Device Dissipation	T_C = 25℃	P_D	80	W
Operating and Storage Junction Temperature Range		T_J, T_{STG}	-65 ~ +125	℃

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Thermal Resistance Junction to Case	θ_{JC}	1.56	℃/W
Thermal Resistance Junction to Ambient	θ_{JA}	62.5	℃/W

Note 1: Pulse Test: Pulse Width = 5.0 ms, Duty Cycle≤10%.
Measurement made with thermocouple contacting the bottom insulated mounting surface of the package (in a location beneath the die), the device mounted on a heatsink with thermal grease applied at a mounting torque of 6 to 8•lbs.

■ ELECTRICAL CHARACTERISTICS (T_C=25℃, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Emitter Sustaining Voltage	$V_{CEO(SUS)}$	I_C=10mA, I_B=0	400			V
Collector Cutoff Current	I_{CBO}	V_{CBO}=700V			0.1	mA
		V_{CBO}=700V, T_C=125℃			1.0	mA
Emitter Cutoff Current	I_{EBO}	V_{EB}=9.0V, I_C=0			100	μA
DC Current Gain	h_{FE1}	I_C=2.0A, V_{CE}=5.0V	8.0		40	
	h_{FE2}	I_C=5.0A, V_{CE}=5.0V	5.0		30	
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	I_C=2.0A, I_B=0.4A			1.0	V
		I_C=5.0A, I_B=1.0A			2.0	V
		I_C=8.0A, I_B=2.0A			3.0	V
		I_C=5.0A, I_B=1.0A, T_C=100℃			3.0	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	I_C=2.0A, I_B=0.4A			1.2	V
		I_C=5.0A, I_B=1.0A			1.6	V
		I_C=5.0A, I_B=1.0A, T_C=100℃			1.5	V
Current-Gain-Bandwidth Product	f_T	I_C=500mA, V_{CE}=10V, f=1.0 MHz	4.0	14		MHz
Output Capacitance	C_{ob}	V_{CB}=10V, I_E=0, f=0.1MHz		80		pF
Resistive Load (Table 1)						
Delay Time	t_D	V_{CC}=125V, I_C=5.0A, I_{B1}=I_{B2}=1.0A, t_p=25μs, Duty Cycle≦1.0%		0.025	0.1	μs
Rise Time	t_R			0.5	1.5	
Storage Time	t_S			1.8	3.0	
Fall Time	t_F			0.23	0.7	

* Pulse Test: Pulse Width≤300μs, Duty Cycle≤2.0%

■ TYPICAL THERMAL RESPONSE

Figure1. Typical Thermal Response



There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate I_C-V_{CE} limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 7 is based on T_C = 25℃; $T_{J(pk)}$ is variable depending on power level. Second breakdown pulse limits are valid for duty cycles to 10% but must be debated when T_C ≥25℃. Second breakdown limitations do not debate the same as thermal limitations. Allowable current at the voltages shown on Figure 7 may be found at any case temperature by using the appropriate curve on Figure 9.

At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.

Use of reverse biased safe operating area data (Figure 8) is discussed in the applications information section.

Table 1. Test Conditions for Dynamic Performance

	REVERSE BIAS SAFE OPERATING AREA AND INDUCTIVE SWITCHING	RESISTIVE SWITCHING
TEST CIRCUITS		
CIRCUIT VALUES		V_{CC}=125V R_C=25Ω D1=1N5820 OR EQUIV

$BV_{CEO(SUS)}$	Inductive Switching	RBSOA
L=10mH R_{B2}=8 V_{CC}=20V $I_{C(pk)}$=100mA	L=20mH R_{B2}=0 V_{CC}=15V R_{B1} selected for desired I_{B1}	L=500mH R_{B2}=0 V_{CC}=15Volts R_{B1} selected for desired I_{B1}



t1 ADJUSTED TO OBTAIN I_C

$t1 \leq \frac{Lcoil(I_{CM})}{V_{CC}}$

$t2 \leq \frac{Lcoil(I_{CM})}{Vclamp}$

TEST EQUIPMENT
SCOPE-TEKTRONIX
475 OR EQUIVALENT

TYPICAL WAVEFORMS





t_r, t_f<10ns
DUTY CYCLE=1.0%
RB AND RC ADJUSTED
FOR DESIRED IB AND I_C

■ TYPICAL CHARACTERISTICS

Figure 2. Base-Emitter Saturation Voltage



Figure 3. Collector-Emitter Saturation Voltage



Figure 4. Collector Saturation Region



Figure 5. DC Current Gain



Figure 6. Capacitance



Figure 7. Maximum Forward Bias Safe Operating Area



■ TYPICAL CHARACTERISTICS

Figure 8. Maximum Reverse Bias Switching Safe Operating Area



Figure 9. Forward Bias Power Derating



Figure 10. Turn-On Time(Resistive Load)



Figure 11. Turn-Off Time (Resistive Load)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.